



防紫外線光管




特性：
內含紫外線吸收膜，減低紫外線對物品退色的影響。
光線波長控制於 360nm 之水平，能夠不吸引蚊蟲。

用途：
適用於印刷行業。


燈座(Lamp base)




電磁波頻譜圖(Spectral energy distribution graphs)




W: 冷白光




N-SDL: 天然白光




EX-N: 三基色天然白光



N-EDL: 天然白光



W-EDL: 冷白光



L-EDL: 暖白光

TOSHIBA 東芝

產品型號	標準包裝 (支/箱)	色溫 (K)	尺寸 (mm)		重量 (g)	燈座	輸出 功率 (w)	電流 (A)	流明 (lm)	演色度 (Ra)	平均壽命 (小時)
			管徑	管長							

普通型


FL20S•N-SDL•NU	25	5,000k	32.5	580	128	G13	20	0.360	850	90	7,500
FL32S•N-SDL•NU	25	5,000k	32.5	830	183	G13	32	0.435	1,460	90	10,000
FL40S•N-SDL•NU	25	5,000k	32.5	1,198	244	G13	40	0.420	2,200	90	10,000
FL40S•W NU	25	4,200k	32.5	1,198	244	G13	40	0.420	2,880	61	10,000

快速起動型

FLR20S•L-EDL/M•A•NU	25	3,000k	32.5	580	128	G13	20	0.360	690	95	7,500
FLR20S•W-EDL/M•A•NU	25	4,200k	32.5	580	128	G13	20	0.360	730	97	7,500
FLR40S•EX-N/M/36•NU-H	25	5,000k	32.5	1,198	244	G13	36	0.440	3,350	84	12,000
FLR40S•L-EDL/M•A•NU	25	3,000k	32.5	1,198	244	G13	40	0.420	1,850	95	10,000
FLR40S•L-EDL/M•NU	25	3,000k	32.5	1,198	244	G13	40	0.420	1,950	95	10,000
FLR40S•N-EDL/M•NU	25	5,000k	32.5	1,198	244	G13	40	0.420	2,050	99	10,000
FLR40S•N-SDL/M•A•NU	25	5,000k	32.5	1,198	244	G13	40	0.420	2,040	90	10,000
FLR40S•N-SDL/M•NU	25	5,000k	32.5	1,198	244	G13	40	0.420	2,180	90	10,000
FLR40S•W/M•NU	25	4,200k	32.5	1,198	244	G13	40	0.420	2,800	61	10,000
FLR40S•W-EDL/M•A•NU	25	4,200k	32.5	1,198	244	G13	40	0.420	1,820	61	10,000
FLR40W/M•A•NU	25	4,200k	38	1,198	332	G13	40	0.435	2,600	61	10,000

高頻率型支架專用

FHF32EX-N•NU	25	5,000k	25.5	1,198	198	G13	32	0.255	3,260	84	12,000
							45	0.425	4,580		



富新工程有限公司
ENGINEERING Fu Sun Engineering Limited

香港北角七姊妹道208號昌利大廈3樓302室
Room 302, 3/F, Cheong Lee Building,
No. 208 Tsz Tsz Mui Road, North Point, HK.

電話: (852)2570-8193 傳真: (852)2571-3150

電郵: enquiry@fusun-toshiba.com

網址: www.fusun-toshiba.com

中國熱線: (86) 135-60702932